



Timber Products Company
THE TREMENDOUS RESOURCE®

Plywood Thickness (in.)	Face Grain Across Supports*									
	5/8 5-Ply (Class-1)		5/8 7-Ply (Struc-1)		11/16 7-Ply (Struc-1)		3/4 5-Ply (Class-1)		3/4 7Ply (Struc-1)	
4	3270	3270	4305	4305	4605	4605	4110	4110	5070	5070
8	1260	1260	1310	1310	1515	1515	1580	1580	1680	1680
12	575	575	580	580	675	675	730	730	745	745
16	265	325	270	330	325	380	370	410	375	420
20	160	210	160	215	195	260	225	285	230	290
24	--	110	--	110	105	135	120	160	120	160

Plywood Thickness (in.)	Face Grain Parallel Supports*									
	5/8 5-Ply (Class-1)		5/8 7-Ply (Struc-1)		11/16 7-Ply (Struc-1)		3/4 5-Ply (Class-1)		3/4 7Ply (Struc-1)	
4	1770	1770	2515	2515	2860	2860	2325	2325	3315	3315
8	635	635	800	865	835	905	895	895	1275	1275
12	210	280	250	330	270	360	460	490	545	675
16		120	105	140	115	155	200	270	240	315
20	--	--	--	100	--	110	145	155	170	210
24	--	--	--	--	--	--	--	100	--	115

Deflection limited to 1/360th of the span, 1/270th where shaded.

* = Plywood continuous across two or more spans.